STATE OF MISSOURI

DEPARTMENT OF NATURAL RESOURCES

MISSOURI CLEAN WATER COMMISSION



MISSOURI STATE OPERATING PERMIT

In compliance with the Missouri Clean Water Law, (Chapter 644 R.S. Mo. as amended, hereinafter, the Law), and the Federal Water Pollution Control Act (Public Law 92-500, 92nd Congress) as amended,

MO-0000388

Permit No.

Owner: Address:	L & P Acquisition L.L.C 5 No. 1 Leggett Road, Carthage, MO 64836							
Continuing Authority: Address:	Same as above Same as above							
Facility Name: Facility Address:	L & P Acquisition L.L.C. – 5 4614 Nash Road, Cape Girardeau, MO 63702							
Legal Description: Latitude/Longitude:	S ½, NE ¼, Sec. 27, T30N, R13E, Cape Girardeau County See page 2							
Receiving Stream: First Classified Stream and ID: USGS Basin & Sub-watershed No.:	Unnamed Tributary to Ditch #1 (U) Ditch #1 (C)(03052) (08020204-010001)							
is authorized to discharge from the faci as set forth herein:	lity described herein, in accordance with the effluent limitations and monitoring requirements							
FACILITY DESCRIPTION								
See page 2								
	discharges under the Missouri Clean Water Law and the National Pollutant Discharge of other regulated areas. This permit may be appealed in accordance with Section 644.051.6 of							
November 30, 2001 July 8, 2005 Effective Date Revised	Doyle Childers, Director, Department of Natural Resources Executive Secretary, Clean Water Commission							
November 29, 2006 Expiration Date MO 780-0041 (10-93)	Edward Galbraith, Director of Staff, Clean Water Commission							

FACILITY DESCRIPTION (continued)

Outfall #001 – Industry - SIC #3069 Non-contact cooling water/storm water Design flow is 600,200 gallons per day Actual flow is rainfall dependent. Latitude/Longitude: +3714325/-08935032

Outfall #002 – Industry – SIC#3069 Storm water/non-contact cooling water/partial collection. Design flow is 5,330 gallons per day. Actual flow is rainfall dependent. Latitude/Longitude: +3714328/-08935080

Outfall #004 – Industry – SIC#3069 Storm water discharge from petroleum products storage area. Design flow is 2,400 gallons per day. Actual flow is rainfall dependent. Latitude/Longitude: +3714322/-08935029

Outfall #005 – Industry – SIC#3069 Storm water discharge from railcar spill containment system. Design flow is 6,280 gallons per day. Actual flow is rainfall dependent. Latitude/Longitude: +3714322/-08935029

A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS

PAGE NUMBER 3 of 6

PERMIT NUMBER MO-0000388

The permittee is authorized to discharge from outfall(s) with serial number(s) as specified in the application for this permit. The final effluent limitations shall become effective upon issuance and remain in effect until expiration of the permit. Such discharges shall be controlled, limited and monitored by the permittee as specified below:

	FINAL EFFLUENT LIMITATIONS			ITATIONS	MONITORING REQUIREMENTS				
OUTFALL NUMBER AND EFFLUENT PARAMETER(S)	UNITS	DAILY MAXIMUM	WEEKLY AVERAGE	MONTHLY AVERAGE	MEASUREMENT FREQUENCY	SAMPLE TYPE			
Outfall #001									
Flow	MGD	*		*	once/month	24 hr. estimate			
Oil & Grease	mg/L	15		10	once/month	grab			
pH – Units	SU	**		**	once/month	grab			
Temperature	°F	***		***	once/month	grab			
MONITORING REPORTS SHALL BE SUBMITTED MONTHLY; THE FIRST REPORT IS DUE January 28, 2002.									
Total Suspended Solids	mg/L	45		30	once/year***	grab			
MONITORING REPORTS SHALL BE SUBMITTED ANNUALLY; THE FIRST REPORT IS DUE October 28, 2002.									
Outfall #002									
Flow	MGD	*		*	once/quarter	24 hr. estimate			
Oil & Grease	mg/L	15		10	once/quarter	grab			
pH – Units	SU	**		**	once/quarter	grab			
MONITORING REPORTS SHALL BE SUBMITTED QUARTERLY; THE FIRST REPORT IS April 28, 2002.									
Biochemical Oxygen Demand	mg/L	45		30	once/year****	grab			

MONITORING REPORTS SHALL BE SUBMITTED <u>ANNUALLY</u>; THE FIRST REPORT IS DUE <u>October 28, 2002.</u> THERE SHALL BE NO DISCHARGE OF FLOATING SOLIDS OR VISIBLE FOAM IN OTHER THAN TRACE AMOUNTS.

B. STANDARD CONDITIONS

IN ADDITION TO SPECIFIED CONDITIONS STATED HEREIN, THIS PERMIT IS SUBJECT TO THE ATTACHED <u>Part I</u> STANDARD CONDITIONS DATED October 1, 1980 AND HEREBY INCORPORATED AS THOUGH FULLY SET FORTH HEREIN.

MO 780-0010 (8/91)

A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS

PAGE NUMBER 4 of 6

PERMIT NUMBER MO-0000388

The permittee is authorized to discharge from outfall(s) with serial number(s) as specified in the application for this permit. The final effluent limitations shall become effective upon issuance and remain in effect until expiration of the permit. Such discharges shall be controlled, limited and monitored by the permittee as specified below:

		FINAL EFF	LUENT LI	MITATIONS	MONITORING REQUIREMENTS	
OUTFALL NUMBER AND EFFLUENT PARAMETER(S)	UNITS	DAILY MAXIMUM	WEEKLY AVERAGE	MONTHLY AVERAGE	MEASUREMENT FREQUENCY	SAMPLE TYPE
Outfall #004						
Flow	MGD	*		*	once/year*****	24 hr. estimate
Total Suspended Solids***	mg/L	100		50	once/year*****	grab
Oil & Grease	mg/L	15		10	once/year*****	grab
pH – Units	SU	*****		*****	once/year*****	grab
Total Petroleum Hydrocarbons	mg/L	*		*		
Outfall #005						
Flow	MGD	*		*	once/year*****	24 hr. estimate
Total Suspended Solids	mg/L	100		50	once/year****	grab
Oil & Grease	mg/L	15		10	once/year*****	grab
pH – Units	SU	******		*****	once/year*****	grab
Total Petroleum Hydrocarbons	mg/L	*		*	once/year****	grab

MONITORING REPORTS SHALL BE SUBMITTED <u>ANNUALLY</u>; THE FIRST REPORT IS DUE <u>October 28, 2002.</u> THERE SHALL BE NO DISCHARGE OF FLOATING SOLIDS OR VISIBLE FOAM IN OTHER THAN TRACE AMOUNTS.

B. STANDARD CONDITIONS

IN ADDITION TO SPECIFIED CONDITIONS STATED HEREIN, THIS PERMIT IS SUBJECT TO THE ATTACHED <u>Part I STANDARD</u> CONDITIONS DATED <u>October 1, 1980</u>, AND HEREBY INCORPORATED AS THOUGH FULLY SET FORTH HEREIN.

A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS (continued)

- * Monitoring requirement only.
- ** pH is measured in pH units and is not to be averaged. The pH is limited to the range of 6.0-9.0 pH units.
- *** Effluent shall not elevate or depress the temperature of the receiving stream beyond the mixing zone more than five (5°)F. The stream temperature beyond the mixing zone shall not exceed ninety (90°)F due to the effluent.
- **** Sample once per year in March.
- ***** Sample once per quarter in the months of January, April, July, and October.
- ***** Sample once per year in April.
- ****** pH is measured in pH units is not to be averaged. The pH is to be maintained at or above 6.0 pH units.

C. SPECIAL CONDITIONS

- 1. This permit may be reopened and modified, or alternatively revoked and reissued, to:
 - Comply with any applicable effluent standard or limitation issued or approved under Sections 301(b)(2)(C) and (D), 304(b)(2), and 307(a) (2) of the Clean Water Act, if the effluent standard or limitation so issued or approved:
 - contains different conditions or is otherwise more stringent than any effluent limitation in the permit; or

 - controls any pollutant not limited in the permit.
 - Incorporate new or modified effluent limitations or other conditions, if the result of a waste load allocation study, (b) toxicity test or other information indicates changes are necessary to assure compliance with Missouri's Water Quality Standards.
 - (c) Incorporate new or modified effluent limitations or other conditions if, as the result of a watershed analysis, a Total Maximum Daily Load (TMDL) limitation is developed for the receiving waters which are currently included in Missouri's list of waters of the state not fully achieving the state's water quality standards, also called the 303(d)

The permit as modified or reissued under this paragraph shall also contain any other requirements of the Clean Water Act then applicable.

- 2. All outfalls must be clearly marked in the field.
- 3. Permittee will cease discharge by connection to areawide wastewater treatment system within 90 days of notice of its availability.
- Changes in Discharges of Toxic Substances 4.

The permittee shall notify the Director as soon as it knows or has reason to believe:

- That any activity has occurred or will occur which would result in the discharge of any toxic pollutant which is not limited in the permit, if that discharge will exceed the highest of the following "notification levels:"
 - (1) One hundred micrograms per liter (100 µg/L);
 - (2) Two hundred micrograms per liter (200 µg/L) for acrolein and acrylonitrile; five hundred micrograms per liter (500 µg/L) for 2,5 dinitrophenol and for 2-methyl-4, 6-dinitrophenol; and one milligram per liter (1 mg/L) for antimony;
 - Five (5) times the maximum concentration value reported for the pollutant in the permit application;
 - The level established in Part A of the permit by the Director.
- That they have begun or expect to begin to use or manufacture as an intermediate or final product or byproduct any (b) toxic pollutant, which was not reported in the permit application.
- 5. Report as no-discharge when a discharge does not occur during the report period.
- 6. General Criteria. The following water quality criteria shall be applicable to all waters of the state at all times including mixing zones. No water contaminant, by itself or in combination with other substances, shall prevent the waters of the state from meeting the following conditions:
 - (a) Waters shall be free from substances in sufficient amounts to cause the formation of putrescent, unsightly or harmful bottom deposits or prevent full maintenance of beneficial uses:
 - Waters shall be free from oil, scum and floating debris in sufficient amounts to be unsightly or prevent full maintenance of beneficial uses:
 - Waters shall be free from substances in sufficient amounts to cause unsightly color or turbidity, offensive odor or (c) prevent full maintenance of beneficial uses:
 - Waters shall be free from substances or conditions in sufficient amounts to result in toxicity to human, animal or (d) aquatic life
 - (e) There shall be no significant human health hazard from incidental contact with the water;
 - There shall be no acute toxicity to livestock or wildlife watering; (f)
 - Waters shall be free from physical, chemical or hydrologic changes that would impair the natural biological (g) community:
 - Waters shall be free from used tires, car bodies, appliances, demolition debris, used vehicles or equipment and (h) solid waste as defined in Missouri's Solid Waste Law, section 260.200, RSMo, except as the use of such materials is specifically permitted pursuant to section 260.200-260.247.